



Boilere electrice uz casnic

GCA 1015 SRC

GCA 1515 SRC

GCU 1015 SRC

GCU 1515 SRC

Boilere electrice - montare deasupra chiuvetei (GCA) si sub chiuveta (GCU)



GCU



GCA



On/Off switch
Buton ON/OFF



Above the sink
installation

**Instalare
deasupra
chiuvetei
(GCA)**



Adjustable room
thermostat

**Termostat
reglabil**



Under the sink
installation

**Instalare
sub
chiuveta
(GCU)**



Informatii principale

Panou de comanda usor de utilizat

Montare usoara deasupra sau sub chiuveta / lavoar.



Caracteristici tehnice GCA 1015 SRC	
Nominal capacity [L] - Capacitate nominala [L]	10 L
Protection of the tank - Protectie boiler electric	Glass ceramic
Rated voltage [V/Hz] - Tensiune de alimentare [V/Hz]	230V/50Hz
Rated power [W] - Putere boiler electric [W]	1500 W
Rated pressure of the water tank - Presiune de lucru [MPa]	0.8 MPa
Insulation [mm] - Izolatie [mm]	19 mm
Heating time from 15°C to 65°C - Incalzire de la 15 la 65 grdC	23 min
Switch On / Off - Buton ON / OFF	Yes
Adjustable thermostat - Termostat reglabil	Yes
Magnesium anode - Anod de magneziu	Yes
Anode tester - Tester anod	No
Safety valve - Supapa de siguranta	Yes
Dimensions H / W / D [m] - Dimensiuni H / L / A [m]	0.410 x 0.370 x 0.250 m
Net weight [kg] - Greutate neta [kg]	6.50 kg
Installation - Montare	deasupra chiuvetei
Warranty (full) - Garantie	2 years

deasupra chiuvetei